



# Band Tag

## A Flush Attachment Method



- For Applications with high temperature metals and rod and wire processing
- Resistant to (see reverse for details):
  - Heat: up to 1800°F (982°C)
  - Chemicals
  - Abrasion
  - UV Exposure
- 3" (76mm) or 4" (103mm) Wide X Customized Length—see reverse for details

- Available as InfoTag® Hi-Temp & Pic-Anneal® .
- Bands thread through slots at the ends of the tags for a flush attachment to your product.
- Able to use the bands you already use to bind your products.
- Pic-Anneal® Band Tag gives rod & wire mills a method to track parts through the entire pickling & annealing process.
- Printed on InfoSight LabelLase® Laser Metal Tag Printers. →
- Preprinted Tags Available.



Find out how easy it is to design and print your tags with a LabelLase® Metal Tag Printer & free Producer™ Software.



PROCESSES VARY—CONTACT US FOR TEST SAMPLES

# Band Tag

## Technical Specifications

	InfoTag® Hi-Temp	Pic-Anneal®
<b>Industry</b>	Industrial manufacturing, distribution, steel mills, titanium mills	Metal rod and wire processing
<b>Typical Customer</b>	Producers of high temperature metals	Rod mills; Wire mills; Wire processing plants; Metals service providers, and Strip Coil producers
<b>Purpose</b>	Rugged barcode-ready identification for harsh environments: resists tearing and detachment during handling, processing, and shipping	Tracking finished and unfinished work pieces through the entire pickling and annealing process
<b>Resistance</b>		
<b>Heat</b>	In excess of 1800°F (982°C)	1800°F (982°C) for 2 hours; 1700°F (926°C) for up to 48 hours
<b>Chemical</b>	Resistant to common solvents	180°F (82°C) in 20% H2SO4 for 2 hours; 100°F (38°C) 24% HCL for 2 hours
<b>Abrasion</b>	Moderate	Moderate
<b>Ultraviolet</b>	Highly resistant to sunlight and fading	Highly resistant to sunlight and fading
<b>Sizes</b>	<b>Width:</b> 3.0 in (76 mm) OR 4.0 in (102 mm) <b>Lengths:</b> to customer specification, not less than 1.0 in (25 mm) <b>Typical Lengths:</b> 6.0 in (152 mm) <b>Slot Size:</b> 1.5" X 1/4" (38mm X 6.3mm)	<b>Width:</b> 3.0 in (76 mm) <b>Lengths:</b> to customer specification, not less than 1.0 in (25 mm) <b>Typical Lengths:</b> 6.0 in (152 mm) <b>Slot Size:</b> 1.5" X 1/4" (38mm X 6.3mm)
<b>Composition</b>	Metal with high contrast laser-markable coatings	Metal with high contrast laser-markable coatings
<b>Available Forms</b>	Print on-site with one of InfoSight's durable, laser metal tag printers or pre-printed by InfoSight	Print on-site with one of InfoSight's durable, laser metal tag printers or pre-printed by InfoSight
<b>Available Colors</b>	Standard white - colors available	Standard white, colors by special order

Technical specifications are subject to change without notice.  
 Producer and "We Barcode Difficult Stuff" are trademarks of InfoSight.  
 LabelLase, InfoTag, and Pic-Anneal are registered trademarks of InfoSight.  
 Copyright 2020 InfoSight Corporation