





## **InfoFusion**<sup>™</sup> **SR**

## **Durability and Rigidity combined with Caustic Survivability**



- For applications in the alumina industry and processes that include exposure to high pH environments
- Resistant to:
  - Heat—200°F (93°C)
  - Chemicals—highly resistant to caustic conditions
  - Abrasion
  - UV Exposure
- 3" (76mm) Wide X Customized Length
- Stainless steel substrate with dual layer polyacrylic laser markable coating
- Ideal for environments with repeated or prolonged exposure to high pH conditions.
- Stainless Steel provides rigidity and rust resistance.
- Polyacrylic layers proves caustic resistance.
- Message is white characters on black background.
- Printed on InfoSight LabeLase® Printers with high contrast alphanumeric characters, graphics, and 1D & 2D barcodes.
  (Fume extractor required.)
- Preprinted tags available.



Find out how easy it is to design and print your tags with a LabeLase® Metal Tag Printer & free Producer<sup>TM</sup> Software.

Tel: +1 (740) 642-3600

www.infosight.com

Email: sales@infosight.com



Contact infosight for samples to test infofusion™sr in your Process

## **InfoFusion**<sup>™</sup> **SR**

## **Technical Specifications**

Industry	Alumina
Typical	Alumina Refinery, Processes that include exposure
Customer	to high pH
Purpose	Identification in high pH environments
Resistance	Heat: up to 200 °F (93°C)
	Chemical: Highly resistant to caustic conditions
	Abrasion: Moderate
	Ultraviolet: Highly resistant to sunlight and fading
	Width: 3.0 in (76 mm)
Sizes	<b>Lengths:</b> to customer specification, not less than 1.0 in (25 mm)
Composition	Stainless steel with dual layer polyacrylic coating
Available	Print on-site with one of InfoSight's durable, laser
Forms	metal tag printers or pre-printed by InfoSight
Available Colors	White characters on black background

