



KettleTag®PLUS

Tags for Fabricators and Galvanizers



- For Galvanizers and Fabricators
- Track pieces through entire galvanizing process
- Resistant to:
 - Heat—1000°F (538°C)
 - Chemicals—caustic & acid rinses, molten zinc bath
 - Abrasion
 - UV Exposure
- 3" Wide (76mm) X Customizable Length
- Metal substrate with laser markable coatings

- ◆ The only tag that survives all 9 steps for galvanizing listed by the American Galvanizers Association.
- ◆ Increase efficiency & reduce handling—tags are applied once and are readable throughout the process.
- ◆ Traceability & error proof installations.
- ◆ Printable with InfoSight LabelLase® Metal Tag Printers. →
- ◆ Preprinted tags are available.



Find out how easy it is to design and print your tags with a LabelLase® Metal Tag Printer & free Producer™ Software.



PROCESSES VARY—CALL TODAY TO TEST KETTLETAG®PLUS IN YOUR PROCESS



KettleTag® PLUS

Technical Specifications

20210823

Industry	Metal galvanizing
Typical Customer	Galvanizers and fabricators
Purpose	Tracking work pieces through the entire galvanizing process
Resistance	Heat: 1000°F (538°C)
	Chemical: 180°F (82°C) in 20% H ₂ SO ₄ for 2 hours; or 100°F (38°C) 24% HCL for 2 hours.
	Abrasion: Moderate
	Ultraviolet: Highly resistant to sunlight and fading
Sizes	Width: 3.0 in (76 mm) Lengths: to customer specification, not less than 1.0 in (25 mm) Typical Lengths: 3.0 in (76 mm)
Composition	Metal with high contrast laser-markable coatings
Available Forms	Print on-site with one of InfoSight's durable, laser metal tag printers or pre-printed by InfoSight.
Available Colors	White and Yellow



Use the QR code to learn about all of our fabricator tags:

Kettletag® PLUS
PaintTag™

ShotTag™
PowderCoat™ Tag

