





## Perma*Flex*™

## As Durable as PermaLabel®, PermaFlex fits the curve of your product



- For Applications requiring lifetime identification on curved surfaces
- Resistant to
  - Heat—1000°F (538°C)
  - Chemicals such as caustics & solvents
  - Abrasion
  - UV Exposure:
- Malleable to conform to curved shapes as small as a 1" radius/ 2" OD
- 3" Wide X Customized Length
- · Aluminum substrate with laser markable coating
- Long term, scratch proof product identification tags.
- Proprietary abrasion resistant technology.
- As durable as PermaLabel® and flexes to conform to the curve of your product.
- Self-adhesive, die-cut, and continuous feed tags available.
- Approved for U.S. Government UID.
- Compatible with all InfoSight Printers.
- Preprinted tags available.



print your tags with a LabeLase®

Metal Tag Printer & free Producer<sup>TM</sup>

Software.

Tel: +1 (740) 642-3600

www.infosight.com

Email: sales@infosight.com



TEST PERMAFLEX® IN YOUR PROCESS—CONTACT US FOR SAMPLES

## Perma*Flex*™

## **Technical Specifications**

Industry	Any operation requiring lifetime equipment asset identification that has curved products or assets.
Typical Customer	Processing plants needing regular power washing; Product ID tags and/or UID labels; Operations needing high quality asset tags
Typical Use	High value asset identification and tracking
Resistance	Heat: 1000°F (538°C)
	Chemical: Withstands caustic power washing, solvents, common vehicle fluids
	Abrasion: Highly resistant
	Ultraviolet: Highly resistant to sunlight and fading (UV topcoat - included)
Sizes	Width: 3.0 in (76 mm) Lengths: to customer specification, not less than 0.75" (19mm) up to 6" (152mm) Special sized and shaped die-cut tags available by special order
Composition	Aluminum with high contrast laser-markable coatings
Available Forms	Print on-site with one of InfoSight's durable, laser metal tag printers or pre-printed by InfoSight.
Available Colors	Burnished bronze only

