





PickleTag[™]

Tags for Rod and Wire Processors



- For applications in metal rod and wire processing
- Resistant to:
 - Heat—1000°F (538°C)
 - Chemicals—Acids, see reverse
 - Abrasion
 - UV Exposure
- 3" (76mm) Wide X Customized Length
- Metal tag with high contrast laser markable coating
- Colors by special order

- Barcodes and text are readable after hot acid baths
- Reduced handling for greater productivity and worker safety
- Readable text and barcodes before and after pickling
- Printed on InfoSight LabeLase® Printers with high contrast alphanumeric characters, graphics, and 1D & 2D barcodes.
- Preprinted tags available.



Find out how easy it is to design and print your tags with a LabeLase® Metal Tag Printer & free ProducerTM Software.

Tel: +1 (740) 642-3600

www.infosight.com

Email: sales@infosight.com



TEST PICKLETAG™ IN YOUR PROCESS—CALL TODAY FOR SAMPLES

PickleTag[™]

Technical Specifications

ng plants;	
ice providers	
rk pieces through a	
O ₄ for 2 hours;	
ight and fading	
Lengths: to customer specification, not less than 1.0 in (25 mm)	
able coatings	
durable, laser metal	
ght	
Ottornal and subits and any bus annuited and an	
Standard white, colors by special order	

